



## **P-Access specifications: power standing wheelchair:**

Rigid steel frame with suspension and front rocking arm with integrated anchorage systems for car transportation.

Length with footplate up : 74 cm / 29"  
Length with footplate down : 105 cm / 41"  
Width with standard armrest : 64,50 cm / 25.40"  
Seat depth: adjustable from 36 cm / 14" to 54 cm / 21.25"  
Seat width : 45 cm / 17.5" with side guards  
Seat high : 50 cm / 20" at front  
Seat angle : minus 3° from front to rear.  
Turning radius : 74 cm

Seat: seat depth adjustment, tight upholstery.

Backrest: electrically adjustable on 32° with tight upholstery.

Chest strap with safety buckle.

Armrest: polyurethane, height adjustment, flip-up backwards.

Footrest: height and angle adjustment, swing up backward.

Knee support: - adjustable in depth, height and width.

Wheel - front: solid maintenance free Ø 200 x 50 mm  
- rear: inflate Ø 360 x 80 mm.

Electronic Dynamic LinX on swing away device.

Motor : 2 DC motors of 350 watts.

Speed : 6 or 10 km/h according local regulation.

Batteries Capacity : 2 x 55 Amp or 2 x 70 Amp

Range : > 20 km or > 30 km

Charger IEB : 8 Amp / 24 volts.

Wheelchair weight - without batteries: 70 kg / 155 lb  
- with batteries 55 Ah : 108 kg / 238 lb  
- with batteries 70 Ah : 122 kg / 270 lb

Maximum user weight : 120 kg / 264lb.

<b>User name :</b>	<b>Size :</b> <b>Weight :</b>	<b>Indicate choice</b>	<b>Retail Euros price without VAT</b>	
<b>P-Access</b>	Max user size : 1.80 m.		<b>7 999</b>	P-00.200/XX
<b>Driving</b>				
	Speed (in km/h)	<b>6 <input type="checkbox"/> ou <input type="checkbox"/> 10</b>	Free of charge	SW
	<b>Attendant control</b>	left <input type="checkbox"/> <input type="checkbox"/> right	800	DLX-AT
	Integrated tray table middle	<input type="checkbox"/>	2 400	HUKA
	Long distance pack : 2x batteries 70 Ah	<input type="checkbox"/>	290	BAT-070-12
	LED road with turning and flashing lights	<input type="checkbox"/>	400	PAC-O-ROAD

<b>Main frame colour</b>	White	<input type="checkbox"/>	Free of charge	P-00.200/WT
	Red Ferrari	<input type="checkbox"/>	Free of charge	P-00.200/RD
	Green anis	<input type="checkbox"/>	Free of charge	P-00.200/GR
	Pink Hello KITTY	<input type="checkbox"/>	Free of charge	P-00.200/PK
	Grey metal	<input type="checkbox"/>	250	P-00.200/GY
	Blue metal with gold glitters	<input type="checkbox"/>	300	P-00.200/BL
	Bronze metal	<input type="checkbox"/>	300	P-00.200/BZ
	Black metal with gold glitters	<input type="checkbox"/>	300	P-00.200/BK
	<b>Special color on request</b> (with RAL code indication)	<input type="checkbox"/>	500	P-00.200/RAL
<b>Battery box colour</b>	Black	<input type="checkbox"/>	Free of charge	P-00.215/BK
	White	<input type="checkbox"/>	Free of charge	P-00.215/WT
	Carbon looking	<input type="checkbox"/>	100	P-00.215/CB
<b>Knee pad support</b>	Regular	<input type="checkbox"/>	Free of charge	P-00.243/M
	Extended (if size > 1.75m)	<input type="checkbox"/>	100	P-00.243/L
	Extra large & comfort kneepad	<input type="checkbox"/>	250	P-97.100/00

<b>Positioning</b>				
	4 points harness (instead of safety belt)	<input type="checkbox"/>	180	Harness-4P-M
	Pectoral bar support with foam protection	<input type="checkbox"/>	160	P-97.125/45
	Foam seat cushion	<input type="checkbox"/> 45x45x8	120	CU-KALLY 46x45x8
	Foam cushion with air controled by valve	<input type="checkbox"/> 40x40x8	350	CU-SK40040080
	Foam cushion with air controled by valve	<input type="checkbox"/> 45x45x8	350	CU-SK45045080
	Physipro contoured backrest with lateral supports	<input type="checkbox"/>	1 200	PH-BACKREST4550
	3 axles contoured headrest	<input type="checkbox"/>	230	Headrest-3axle-std
	Headrest support bar (between push handles)	<input type="checkbox"/>	210	HA-KO-ALU-C22
	Footrest riser (+28 mm)	<input type="checkbox"/> x1 ou <input type="checkbox"/> x2	35	P-00.240/00
	Heel strap (pair)	<input type="checkbox"/>	100	P-00.234/00
	Ankle belt	<input type="checkbox"/> S - <input type="checkbox"/> M - <input type="checkbox"/> L	200	Anke-Belt-X

<b>Accessories</b>				
	Flip-up tray table	left <input type="checkbox"/> <input type="checkbox"/> right	590	P-97.120/45
	WISTOP: distance "stop and go" controller	<input type="checkbox"/>	900	WISTOP
	Pair of notched anti-puncture tires at rear	<input type="checkbox"/>	200	Tire-insert 300-8-GR
	Black tires (set of 4)	<input type="checkbox"/>	160	-

**Default selection**     **option to be checked if different choice.**

**Sales conditions:** Ex-works factory: pre-payment before shipment.

Any order implies full acceptance of the general terms and conditions of sale online at [www.4power4-powerstand.com](http://www.4power4-powerstand.com).

Company name : ..... **VAT #:** .....

Contact name : .....

e.mail : .....

GSM : .....

**Date, signature, company seal &**