



P-eStand specifications: power standing wheelchair:

Rigid steel frame with suspension and front rocking arm with integrated anchorage systems for car transportation.

Automatic locking rocking arm when standing.

Modular backrest with rigid seat adjustable in depth.

Overall length raised footrest: 89 cm

Overall length unfolded footrest: 102 cm Standard configuration width: 68 cm.

Seated height: <50 cm at the front, slope >3°.

Seat width: 40 - 46 - 50 cm.

Seat depth: adjustable from 40 to 50 cm every 2 cm.

Turning radius: 75 to 80 cm depending on seat depth selection.

Modular backrest, electrically tiltable from -5° at the front to + 40° at the rear.

3-axis headrest.

Bust strap with safety buckle / harness Ergonomic PU armrest, adjustable height, rearward liftable.

Footrest: height adjustable, liftable on the back.

Front wheel Ø 200 x 50 mm with maintenance-free bandage.

Rear wheel Ø 360 x 80 mm inflatable and suspended.

Ergonomic knee pad adjustable in depth, height, spacing.

High beams and turn signals.

Dynamics LinX-A400 electronics with Bluetooth  control and integrated USB  port.

Safety device allowing a return to a sitting position.

Motorization: electric propulsion: 2 AMT SCHMID motors of 350 watts.

Speed: 6 or 10 km/h depending on version.

Battery capacity:

- 2 AGM x 44 Ah-12 volts batteries (approved IATA air transport). Range: > 20 km > 25 km.
- 60 Ah lithium LiFePO. Range: > 25 km > 35 km.
- - Charger 8 Ah.

Weight of the chair without battery: 83 kg, with GEL batteries 108 kg, with lithium battery 99 kg.

Maximum user weight: 120 kg.



P-eStand - RWD

Order form 2022

info@powerstand.eu

User name :	Size : Weigh :	Indicate choice	Retail Euros price without VAT	
P-eSTAND		■	14 000	P-03.000/00
Speed	(en km/h)	6 <input type="checkbox"/> or ■ 10	Free of charge	
Remote control	swing away side	L <input type="checkbox"/> or ■ R	Free of charge	SW/L-R
Remote control integrated inside the tray table		<input type="checkbox"/>	2 400	HUKA
Modular seat and Physipro backrest		■ H50 <input type="checkbox"/> H60	Free of charge	PH-BACKREST4550 PH-BACKREST4560
Seat width (in cm)		40 – 46 - 50		
Seat depth (in cm)		40 – 42 – 44 – 46 – 48 - 50		
Rear anti-tips position		Front – Middle - Rear		
Armrest height (above seat sheet in cm)		■ 23 - <input type="checkbox"/> 28		
Foam seat cushion		■ 46 x 45 x 8	Free of charge	CU-KALLI
Foam & air cushion controled by valve		<input type="checkbox"/> 40 x 40 x 8	330	CU-SK40040080
Foam & air cushion controled by valve		<input type="checkbox"/> 45 x 45 x 8	330	CU-SK45045080
Driving				
Attendant control		L <input type="checkbox"/> or ■ R	800	DLX-AT
WISTOP : stop in the distance		<input type="checkbox"/>	800	WISTOP
Pack batteries GEL 2x44 Ah IATA approved		■	500	BAT-044-12-AGM
1x60 Ah battery Lithium LiFePO		<input type="checkbox"/>	800	BAT-060-24-LIFEPO4
Colour				
Fairing colours	White	■		P-03.050/WT
	Red Ferrari	<input type="checkbox"/>		P-03.050/RD
	Green anis	<input type="checkbox"/>		P-03.050/GR
	Carbone	<input type="checkbox"/>		P-03.050/CB
	Yellow	<input type="checkbox"/>		P-03.050/YL
	Orange	<input type="checkbox"/>		P-03.050/OG
	Blue metal	<input type="checkbox"/>		P-03.050/BL
	Bronze metal	<input type="checkbox"/>	250	P-03.050/BZ
	Black	<input type="checkbox"/>		P-03.050/BK
Special colour on request (with RAL indication)		<input type="checkbox"/>	500	P-03.050/RAL
Positioning				
Special armrest with truck support		<input type="checkbox"/>	1 500	P-97.201/00
Tight wedge		<input type="checkbox"/>	580	PH-WEDGE
4 points harness (instead od safety belt)		<input type="checkbox"/>	180	Harness-4P-M
4 points comfort harness		<input type="checkbox"/>	210	
	Male	<input type="checkbox"/> - S	<input type="checkbox"/> - M	<input type="checkbox"/> - L
	Female	<input type="checkbox"/> - S	<input type="checkbox"/> - M	<input type="checkbox"/> - L
Dynamic ankles belt (pair)		<input type="checkbox"/> S- <input type="checkbox"/> M- <input type="checkbox"/> L	190	ANKLE-BELT
Accessories				
Push handles based on bicycle type		<input type="checkbox"/>	120	P-97.304/00
Tray table flip-up on		L ■ or <input type="checkbox"/> R	590	P-97.120/xx
Back bag		<input type="checkbox"/>	190	BACK-BAG
Compatible MkII DAHL dock station		<input type="checkbox"/>	Price on request	-
Tires				
Pair of grey nothched anti-puncture Ø300-8 tires		<input type="checkbox"/>	200	Tire-Insert 300-8-GR
Black tires (set of 4)		<input type="checkbox"/>	180	

■ Default selection option to be checked if different choice

Sales conditions: Ex-works factory: pre-payment before shipment.

Any order implies full acceptance of the general terms and conditions of sale online at www.4power4-powerstand.com.

Company name : **VAT #:**.....
 Contact name :
 e.mail : **GSM :**

Date, signature & company seal