



P-eStand specifications: power standing wheelchair:

Rigid steel frame with suspension and front rocking arm with integrated anchorage systems for car transportation.

Automatic locking rocking arm when standing.

Modular backrest with rigid seat adjustable in depth.

Overall length raised footrest: 89 cm

Overall length unfolded footrest: 102 cm Standard configuration width: 68 cm.

Seated height: <50 cm at the front, slope >3°.

Seat width: 40 - 46 - 50 cm.

Seat depth: adjustable from 40 to 50 cm every 2 cm.

Turning radius: 75 to 80 cm depending on seat depth selection.

Modular backrest, electrically tiltable from -5° at the front to + 40° at the rear.

3-axis headrest.

Bust strap with safety buckle / harness Ergonomic PU armrest, adjustable height, rearward liftable.

Footrest: height adjustable, liftable on the back.

Front wheel Ø 200 x 50 mm with maintenance-free bandage.

Rear wheel Ø 360 x 80 mm inflatable and suspended.

Ergonomic knee pad adjustable in depth, height, spacing.

High beams and turn signals.

Dynamics LinX-A400 electronics with Bluetooth  control and integrated USB  port.

Safety device allowing a return to a sitting position.

Motorization: electric propulsion: 2 AMT SCHMID motors of 350 watts.

Speed: 6 or 10 km/h depending on version.

Battery capacity:

- - 60 Ah lithium LiFePO. Range: > 25 km > 35 km

- - Charger 8 Ah.

Weight of the chair without battery: 83 kg, with GEL batteries 108 kg, with lithium battery 99 kg.

Maximum user weight: 120 kg.



P-eStand - RWD
 Order form 2024
info@powerstand.eu

| User name : | Size : Weigh : | Indicate choice | Retail Euros price without VAT | |
|---|----------------------------|--|------------------------------------|------------------------------------|
| P-eSTAND | | ■ | 15 000 | P-03.000/00 |
| Speed | (en km/h) | 6 <input type="checkbox"/> or ■ 10 | Free of charge | |
| Remote control | swing away side | L <input type="checkbox"/> or ■ R | Free of charge | SW/L-R |
| Remote control integrated inside the tray table | | <input type="checkbox"/> | 2 400 | HUKA |
| Modular seat and Physipro backrest | | ■ H50 <input type="checkbox"/> H60 | Free of charge | PH-BACKREST4550 PH-BACKREST4560 |
| Seat width (in cm) | | | 40 - 46 - 50 | |
| Seat depth (in cm) | | | 40 - 42 - 44 - 46 - 48 - 50 | |
| Rear anti-tips position (circle the position) | | | Front - Middle - Rear | |
| Armrest height (above seat sheet in cm) | | | ■ 23 - <input type="checkbox"/> 28 | |
| Foam seat cushion | | ■ 46 x 45 x 8 | Free of charge | CU-KALLI |
| Foam & air cushion controled by valve | | <input type="checkbox"/> 40 x 40 x 8 | 350 | CU-SK40040080 |
| Foam & air cushion controled by valve | | <input type="checkbox"/> 45 x 45 x 8 | 350 | CU-SK45045080 |
| Driving | | | | |
| Attendant control | | L <input type="checkbox"/> or ■ R | 900 | DLX-AT |
| WISTOP : stop in the distance | | <input type="checkbox"/> | 900 | WISTOP |
| 1x60 Ah battery Lithium LiFePO (with gauge) | | ■ | | BAT-060-24-LIFEPO4 |
| Colour | | | | |
| Fairing colours | White | ■ | | P-03.050/WT |
| | Red Ferrari | <input type="checkbox"/> | | P-03.050/RD |
| | Green anis | <input type="checkbox"/> | | P-03.050/GR |
| | Carbone looking | <input type="checkbox"/> | 300 | P-03.050/CB |
| | Yellow | <input type="checkbox"/> | | P-03.050/YL |
| | Orange | <input type="checkbox"/> | | P-03.050/OG |
| | Blue metal | <input type="checkbox"/> | | P-03.050/BL |
| | Bronze metal | <input type="checkbox"/> | 300 | P-03.050/BZ |
| | Black | <input type="checkbox"/> | | P-03.050/BK |
| Special colour on request (with RAL indication) | | <input type="checkbox"/> | 500 | P-03.050/RAL |
| Positionning | | | | |
| Special armrests with truck support | | <input type="checkbox"/> | 1 500 | P-97.201/00 |
| Tight wedge | | <input type="checkbox"/> | 580 | PH-WEDGE |
| 4 points harness (instead of safety belt) | | <input type="checkbox"/> | 180 | Harness-4P-M |
| 4 points comfort harness | | <input type="checkbox"/> | 220 | |
| | Male | <input type="checkbox"/> - S | <input type="checkbox"/> - M | <input type="checkbox"/> - L |
| | Female | <input type="checkbox"/> - S | <input type="checkbox"/> - M | <input type="checkbox"/> - L |
| | Dynamic ankles belt (pair) | <input type="checkbox"/> S- <input type="checkbox"/> M- <input type="checkbox"/> L | 190 | ANKLE-BELT |
| Accessories | | | | |
| Push handles (based on bicycle type) | | <input type="checkbox"/> | 120 | P-97.304/00 |
| Tray table | flip-up on | L ■ or <input type="checkbox"/> R | 590 | P-97.120/xx |
| Back bag | | <input type="checkbox"/> | 190 | BACK-BAG |
| Compatible MkII DAHL dock station | | <input type="checkbox"/> | Price on request | - |
| Tires | | | | |
| Pair of grey notched anti-puncture Ø300-8 tires | | <input type="checkbox"/> | 220 | Tire-Insert 300-8-GR |
| Black tires (set of 4) | | <input type="checkbox"/> | 180 | |

■ Default selection option to be checked if different choice

Sales conditions: Ex-works factory: pre-payment before shipment.

Any order implies full acceptance of the general terms and conditions of sale online at www.4power4-powerstand.com.

Company name :.....**VAT #:**.....
 Contact name :.....
 e.mail :.....**GSM :**.....

Date, signature & company seal