



Chair with electric middle drive and electric standing with double biometric compensation of the back and leg.

- ▶ Rigid steel frame with integrated taxi-hitch.
- ▶ Electric traction with gyroscopic stabilization.
- ▶ Articulated rear spreader bar with angular limitation.
- ▶ Front wheel Ø 360 x 80 mm inflatable and suspended.
- ▶ Rear wheel Ø 200 x 50 mm maintenance-free tyre mounted on spreader bar with integrated anti-sway.
- ▶ Ergonomic armrests adjustable in height and retractable to the rear for easy transfer.
- ▶ Modular seat with rigid backrest, height 50 cm, electrically tiltable over 50° from +5° to -45°.
- ▶ Electric backrest with biometric compensation.
- ▶ Ergonomic headrest adjustable in 3 axes (height, tilt and depth).
- ▶ Chest strap with safety buckle.
- ▶ Footrest: bi-pallet adjustable in height, liftable on the back with heel strap.

Single-pallet optional.

- ▶ Electric leg rest with biometric compensation.
- ▶ Ergonomic central T-shaped kneepads, adjustable for depth, height, spread and tilt.
- ▶ Overall length footrest raised: 97 cm.
- ▶ Seated length overall unfolded footrest: 123 cm
- ▶ Standing length excluding all unfolded footrest: 104 cm
- ▶ Overall width: 64 cm
- ▶ Turning radius: 73.50 cm
- ▶ Rigid seat adjustable in depth and width.
- ▶ Seat height: <49 cm in front, slope >3° towards the back.
- ▶ Seat width and depth: adjustable every 2 cm from 40 to 50 cm.
- ▶ Dynamics Control LinX A400 electronics with Bluetooth and integrated USB port.
- ▶ Integrated tilt sensor in the frame prohibiting standing up out of flat surface.
- ▶ Tilt sensor integrated in the seat limiting the speed when standing up.
- ▶ Safety device allowing a return to the seated position in case of electronics failure.
- ▶ LED road lighting kit with front and rear direction indicators.
- ▶ Motorization: 2 AMT SCHIMD 350 watt motors.
- ▶ Speed: 6 or 10 km/h depending on version.
- ▶ 70 Amp/24 volt lithium battery (not air transportable).
- ▶ Autonomy: from 25 km to 30 km depending on driving conditions.
- ▶ Charger: 8 Amp/24 volt lithium battery charger.
- ▶ Weight of the chair with batteries: approximately 113 kg.
- ▶ Maximum user weight: 120 kg.



P6-Compact - MWD

Order Form 2024

info@powerstand.eu

User name :	Size : Weight :	Indicate choice	Retail €uros price without VAT	
P-Compact		<input type="checkbox"/>	19 500	P-02.000/00
Inside version	Rear wheel Ø200	<input type="checkbox"/>		P-02.004/51
Outside version	Rear wheel Ø230 +4 cm	<input checked="" type="checkbox"/>		P-02.004/56
	Speed in km/h	6 <input type="checkbox"/> or <input checked="" type="checkbox"/> 10	Free of charge	
	Swing away	L <input type="checkbox"/> or <input checked="" type="checkbox"/> R	Free of charge	P-97.250/00-L or R
Remote control integrated inside the tray table		<input type="checkbox"/>	2 400	
Modular seat and Physipro backrest		<input checked="" type="checkbox"/> H50 <input type="checkbox"/> H60	Free of charge Free of charge	PH-BACKREST 4550 PH-BACKREST 4560
Seat width (in cm)		40 – 42 – 44 – 46 – 48 – 50		
Seat depth (in cm)		40 – 42 – 44 – 46 – 48 – 50		
Backrest height (continu ajustement)		N/A		
Armrest height (above seat)		<input checked="" type="checkbox"/> 23 - <input type="checkbox"/> 28		
Foam seat cushion		<input checked="" type="checkbox"/> 46 x 45 x 8	Free of charge	CU-KALLI
Foam & air cushion controlled by valve		<input type="checkbox"/> 40 x 40 x 8	350	CU-SK40040080
Foam & air cushion controlled by valve		<input type="checkbox"/> 45 x 45 x 8	350	CU-SK45045080
Driving				
Attendant control		L <input type="checkbox"/> or <input checked="" type="checkbox"/> R	800	DLX-AT
WISTOP : emergency stop at distance		L <input type="checkbox"/> or <input checked="" type="checkbox"/> R	800	WISTOP
Air transportation : Pack 2 batteries GEL IATA 44 Ah & charger		<input type="checkbox"/>	500	BAT-44-12-GEL BAT-CHARG-08
Colour				
	White	<input checked="" type="checkbox"/>		P-02.252/WT
	Red Ferrari	<input type="checkbox"/>		P-02.252/RD
	Green anis	<input type="checkbox"/>		P-02.252/GR
	Carbone	<input type="checkbox"/>		P-02.252/CB
	Yellow	<input type="checkbox"/>		P-02.252/YL
	Orange	<input type="checkbox"/>		P-02.252/OR
	Blue metal	<input type="checkbox"/>		P-02.252/RD
	Bronze metal	<input type="checkbox"/>	250	P-02.252/GR
	Black	<input type="checkbox"/>		P-02.252/BK
Special colour on request (with RAL indication)		<input type="checkbox"/>	500	P-02.252/RAL
Positionning				
Special armrest with truck support		<input type="checkbox"/>	1 500	P-97.201/00
Pectoral bar support with foam protection		<input type="checkbox"/>	180	P-97.125/XX
Tight wedge		<input type="checkbox"/>	580	PH-WEDGE
4 points harness (instead od safety belt)		<input type="checkbox"/>	180	HARNESS-4P-M
4 points comfort harness		<input type="checkbox"/>		
	Male	<input type="checkbox"/> S - <input type="checkbox"/> M - <input type="checkbox"/> L	210	PH-HARNESS-4P-M
	Female	<input type="checkbox"/> S - <input type="checkbox"/> M - <input type="checkbox"/> L	210	PH-HARNESS-4P-F
Dynamic ankles belt (pair)		<input type="checkbox"/> S - <input type="checkbox"/> M - <input type="checkbox"/> L	190	ANKLE-BELT
Strap belt		<input type="checkbox"/>	100	P-00.234/00
Accessoires				
Push handles based on bicycle type		<input type="checkbox"/>	120	P-97.304/00
Tray table flip-up on		L <input checked="" type="checkbox"/> or <input type="checkbox"/> R	590	P-97.120/XX
Foot-plate single version		<input type="checkbox"/>	90	P-97.001/00
Back bag		<input type="checkbox"/>	190	BACK-BAG
Compatible MkII DAHL dock station		<input type="checkbox"/>	Price on request	
Tires				
Pair of grey notched anti-puncture Ø300-8 tires at rear		<input type="checkbox"/>	220	TIRE-Insert 300-8-GR
Black tires (set of 6)		<input type="checkbox"/>	270	

Default selection **option to be checked if different choice.**

Sales conditions: Ex-works factory: pre-payment before shipment.

Any order implies full acceptance of general terms and conditions of sale online at www.4power4-powerstand.com.

Company name : **VAT #:**.....
 Contact name :
 e.mail : **GSM :**.....

Date, signature & company seal